

WHAT IS CLAIMED IS:

- 5 1. A method for processing meat products comprising:
providing a first member comprising a first surface
defining a concavity and comprising a plurality of protrusions
extending from said first surface and arranged in a first
pattern;
10 providing a second member comprising a second
surface defining a concavity comprising a plurality of
protrusions extending from said second surface and arranged in
a second pattern;
providing a meat product;
15 sandwiching the meat product between the first and
second surfaces impressing the first and second patterns on
the meat product;
heating the meat product within the two members for
cooking the impressed patterns on the meat product;
20 removing the impressed meat product from the two
members; and
cooking the meat product to a desired state.

- 25 2. A method as recited in claim 1 further comprising
packaging the meat product in a film prior to sandwiching the
meat product between the two members, wherein sandwiching
comprises sandwiching the packaged meat product between the
two members impressing the first and second patterns on the
meat product, and wherein heating comprises heating the
30 packaged meat product within the two members for cooking the
impressed patterns on the packaged meat product.

3. A method as recited in claim 1 wherein the first and
second patterns are the same.

1 47607/CM/C945

4. A method as recited in claim 1 wherein heating
comprises immersing the two members with meat product in hot
5 water.

5. A method as recited in claim 1 wherein heating
comprises electrically heating the two members.

10 6. A method as recited in claim 1 wherein heating
comprises applying heat to the two members.

7. A method as recited in claim 1 wherein heating
comprises applying steam to the two members.

15 8. A method as recited in claim 1 further comprising
pivotally coupling the first member to the second member.

9. A method as recited in claim 1 wherein sandwiching
20 comprises applying hydraulic pressure on one of said first and
second members.

10. A method as recited in claim 1 wherein providing a
first member comprises providing a member having a plurality
25 of longitudinal protrusions and a plurality of lateral
parallel protrusions.

11. A method as recited in claim 1 further comprising:
positioning a conveyor having a belt over a
30 container containing hot water; and

coupling the two members on the conveyor belt,
wherein cooking the meat product within the two members
comprises rotating the conveyor belt to submerge the members
into the hot water.

35

1 47607/CM/C945

12. A method as recited in claim 11 further comprising:
providing a third member coupled to the conveyor
5 belt comprising a third surface defining a concavity and
comprising a plurality of protrusions extending from the third
surface and arranged in a third pattern;

providing a fourth member coupled to the conveyor
belt comprising a fourth surface defining a concavity and
10 comprising a plurality of protrusions extending from the
fourth surface and arranged in a fourth pattern;

rotating the conveyor belt placing the third and
fourth members over the water in the container;

packaging a second meat product in a film;
15 placing the second packaged meat product between the
third and fourth surfaces;

sandwiching the second packaged meat product between
the third and fourth surfaces impressing the third and fourth
patterns on the second packaged meat product; and

20 rotating the conveyor belt placing the third and
fourth members in the hot water for cooking the impressed
third and fourth patterns on the second packaged meat product.

13. A method as recited in claim 12 wherein when the
25 first and second members are not in the hot water, the third
and fourth members are submerged in the hot water.

~~14.~~ A method for processing meat products comprising:
providing a first member having a plurality of first
30 depressions each first depression comprising a plurality of
protrusions;

providing a second member having a plurality of
second depressions corresponding to the plurality of first
depressions, each of the second depressions comprising a
35 plurality of protrusions;

1 47607/CM/C945

placing meat products in each of said plurality of first depressions;

5 aligning the first member with the second member wherein each of said first depressions is aligned with a second depression;

sandwiching the first and second members impressing the protrusions of a first and second depression on each of
10 said meat products forming impressions on the outer surfaces of the meat products;

heating the meat products within the two members for cooking the impressions on the meat products; and

15 removing the meat products from the two members.

15. A method as recited in claim 14 further comprising cooking the meat products to a desired state.

16. A method as recited in claim 14 further comprising
20 packaging the meat products in a film prior to sandwiching the meat product between the two members, wherein sandwiching comprises sandwiching the packaged meat products between the two members impressing the protrusions of the first and the second depression on said meat products forming impressions on
25 the outer surfaces of the meat products, and wherein cooking comprises cooking the packaged meat products within the two members for cooking the impressions on the packaged meat products.

30 17. A method as recited in claim 16 further comprising cooking the packaged meat products to a desired state.

18. A method as recited in claim 14 wherein sandwiching
35 comprises applying hydraulic pressure on one of said first and

second members against the other of said first and second members.

5

19. A method as recited in claim 14 wherein each of the first depressions and second depressions comprise a plurality of longitudinal protrusions and a plurality of lateral parallel protrusions.

10

20. A method as recited in claim 14 wherein heating comprises electrically heating the first and second depressions.

15

21. A method for processing a meat product comprising:
packaging the meat product;
providing an impression on the packaged meat product outer surface while packaged;
heating the packaged meat product to cook the impression on the meat product outer surface; and
cooking the meat product to a desired state.

20

22. A method as recited in claim 21 wherein providing an impression comprises sandwiching the meat product in a compartment of an impression device having protrusions which impress into the packaged meat product outer surface.

25

23. A method as recited in claim 22 wherein heating comprises heating the device.

30

24. A method as recited in claim 23 further comprising removing the packaged meat product from the device after heating and before cooking.

35

1 47607/CM/C945

25. A method as recited in claim 24 further comprising
providing a cooking device separate from the impression device
5 for cooking the meat product to a desired state.

10

15

20

25

30

35